

IP Bullet Camera 5MP IR Bullet CAMERA



The WBC0E-CLIB5R3FM is a 5MP fixed 3.6 mm lens IR Bullet Camera. This Camera is outdoor ready IP 66 rated and having IR up to 30 mtrs, can support max 128 GB SD card. The camera gives an excellent choice for Small to Mid-size applications at an affordable price.

- 3.6mm lens
- 2 IR Array LEDS
- IR Distance (30m)
- IP 66, Metal Body
- SD – 128 GB
- POE : IEEE 802.3af
- 12VDC
- 3 years warranty

PART# : WBC0E-CLIB5R3FM

Length : 157(W) x 70(H) X 60(D)mm

Weight : 650g

Auth. Project Partner :



Specifications

Model	WBC0E-CLIB5R3FM
Camera	
Image Sensor	1/2.7" OV High-resolution CMOS Sensor
Resolution	5MP
Main Stream 1	2592*1944@20fp, 2560*1920@20fp
Main Stream 2	2560*1440@25fp
Main Stream 3	1920*1080 @ 25 FPS, 1280*720 @ 25 FPS
Sub Stream 1	720*480 @ 15 FPS, 720*480 @ 25 FPS
Tri Stream	352*288 @ 15 FPS, 352*288 @ 25 FPS
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Lens	
Focus Length	3.6mm
Lens Type	Fixed
Night Vision	
Infrared LED	42μ x 2 PCS
Infrared Distance	30M
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iphone ,Android
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
Corridor Pattern	Support
Defog Mode	Support
DWDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands

Auth. Project Partner :



Specifications

Interface	
SD Card Slot	Support Max 128GB
General	
Housing	Metal , IP66
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 900mA
Dimension	157(W) x 70(H) x 66(D)mm
Weight	650g

Auth. Project Partner :



Solutions Design | Supply | Installations | AMC | Services

TECHNOHEAD Security IT & Telecom Projects LLP

Address :- 706 Siddharth Building 96, Nehru Place, New Delhi – 110019, India

Mobile :- +91 8527590286, 9312286189

Email :- info@technohead.in Website : www.technohead.in