

IP Dome Camera 5MP IR Dome CAMERA



The WBC0E-CLID5R2FS is a 5MP fixed 3.6 mm lens IR dome Camera. This Camera is outdoor ready IP 66 rated and having IR up to 20 mtrs, can support max 128 GB SD card. The camera gives an excellent choice for Small to Mid-size applications at an affordable price.

- 3.6mm lens
- 18 LEDS
- IR Distance (20m)
- IP 66, Metal Body
- SD – 128 GB
- POE : IEEE 802.3af
- 12VDC
- 3 years warranty

PART# : WBC0E-CLID5R2FS

Length : ϕ 94.5 x 76(H) mm

Weight : 450g

Auth. Project Partner :



Specifications

Model	WBC0E-CLID5R2FS
Camera	
Image Sensor	1/2.7" OV High-resolution CMOS Sensor
Resolution	5MP
Main Stream 1	2592*1944@20fps, 2560*1920@20fps
Main Stream 2	2560*1440@25fps
Main Stream 3	1920*1080@25fps, 1280*720@25fps
Sub Stream 1	720*480@15fps, 720*480@25fps
Tri Stream	352*288 @ 15 FPS, 352*288 @ 25fps
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Lens	
Focus Length	3.6mm
Lens Type	Fixed
Night Vision	
Infrared LED	14μ x 18 PCS
Infrared Distance	20M
Network	
Ethernet Protocol	RJ-45 (10/100Base-T)
ONVIF	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMT
P2P	Support ONVIF 2.4
POE	YES, Support QR Code
IE Brower	Support IEEE 802.3af
Smart Phone	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Camera Features	iphone ,Android
Day/Night	
Image Configuration	Color/ B&W (IR-CUT) Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
Corridor Pattern	Support
Defog Mode	Support
DWDR	Support
Motion	Support
Detection Privacy	3 Rectangular Zone
Masking	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands

Auth. Project Partner :



Specifications

Interface	
SD Card Slot	Support Max 128GB
General	
Housing	Metal , IP66
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 850mA
Dimension	Φ 94.5 x 76(H) mm
Weight	450g

Auth. Project Partner :



Solutions Design | Supply | Installations | AMC | Services

TECHNOHEAD Security IT & Telecom Projects LLP

Address :- 706 Siddharth Building 96, Nehru Place, New Delhi – 110019, India

Mobile :- +91 8527590286, 9312286189

Email :- info@technohead.in Website : www.technohead.in

