



<b>General Parameters</b>	Sensor Type and Size	1 / 2.8" SONY CMOS (Exmor Technology STARVIS Series)
	Minimum Illumination(B/W)	0 Lux with IR LED on
	Minimum Illumination(Color/Monochrome)	0.08 Lux @ F2.0 @ 1/25s, No Sens-up allowed
	Lens Type	Fixed Iris
	Focal length	6mm
	HFOV (degrees)	52°
	Shutter Speed	1/12500s to 1/25s
	SNR	<b>48db @ 5lux</b>
	Lens mount	M12 x 0.5
	Minimum Object Distance	0.3 m
	Aperture	F 1.2
<b>Infrared</b>	IR LED type	4 - Array LEDs
	IR range	20m
<b>Image &amp; Video</b>	Video Compression	H.265/H.264/MJPEG
	Resolutions	2048*1536(3MP)/1080p(2MP)/720p/D1/2CIF/CIF/QCIF
	Stream Profiles	Four streams are supported Profile 1: - 3MP @ 30fps(H.265/H.264) Profile 2: - D1 @ 30fps(H.265/H.264) Profile 3: - D1 @ 5fps(MJPEG) Profile 4: - 720p @ 30fps(H.265/H.264/MJPEG)
	Max. number of simultaneous streams	<b>4</b>
	Stream type	Unicast/Multicast
	Bitrate	512Kbps - 4Mbps
	Frame Rate	1 - 30fps
	Network Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, <b>ONVIF S</b>
	Image Enhancements	Saturation/ contrast/Brightness/Hue/Sharpness/Rotate
WDR	<b>True WDR (120db)</b>	

	Image Features	ROI, Edge Recording, Network Recording, Day/Night Settings (Auto / Manual), 3DNR, True WDR, DWDR, E-PTZ, BLC, Digital Zoom, Image Snapshots, White Balance (Auto/Fluorescent/Incandescent/Sunny), Adaptive Streaming, Smart Streaming (Max. 3 Windows), Unicast/Multicast, 2DNR (Auto/Manual)
<b>Events &amp; Actions</b>	Events	Motion detection, View Tamper, Line intrusion / Directional motion / Trip Wire, Zone Intrusion, IP-Conflict, Network-Disconnect, Storage Alert,
	Actions	Email / TCP / SMS Notifications, Alarm Recording, Image/Clip Upload
<b>Hardware Interface</b>	Communication Interface	1 RJ45 10/100Mbps Ethernet Interface
	SD Card	<b>Up to 128 GB</b>
	Processor & RAM	HI-3516A & 4 GB
<b>Electrical</b>	Power Supply	12V/2A, Poe (802.3af)
	Power Consumption	Less than 7 W
<b>Environmental Mechanical</b>	Operating Temperature/ Storage Temperature	0 to 50 Degree / (-)20 to 60 Degree
	Operating Humidity	Less than 90% RH
	Certifications	CE, IP66, FCC Part-15 Class-B
	Dimension	320 X 84.5 X 92.5mm (L X H X W)
	Weight & Color	920gm & White (Beige)
	Material Type	Aluminum