



Video	Input	Supports up to 24 IP channels
	Compression	H.265(Only for Web Client) /H.264/ MPEG4/Motion JPEG
	Output	1 HDMI, 1 VGA
Audio	Compression	G.711(for two-way audio), G.726, AAC, PCM
Alarm	Input	4
	Output	1
Display	Split (VGA/HDMI)	1x1, 2x2, 3x3, 4x4, 1+5, 1+7, 3+4, 2+8, 1+12, 1⊕+12, 1+9, 4+9,2+12 and Sequential
	Split (Through LAN)	24 Channel @ 1080P/720P/D1
	Resolution(VGA/HDMI)	6 Ch.@1080P, 9 Ch.@ 720P and 16 Ch.@ D1
	Privacy Masking	Yes
	Digital Zoom on Live	Yes
	Snapshot	Yes
	Multiple Camera Viewing	Through Cascading (up to 20 Devices)
	OSD	Channel Number and Name, Status, Video Loss, Motion Detection, Recording, View Tamper and Disabled Channel (As per camera support)
Recording	Frame Rate	25fps
	Image Resolution	1080P, 720P, D1
	Pre-Record	Up to 30 Sec
	Post-Record	10-300 Sec
	Snapshot Format	JPEG
	Recording Modes	Continuous, Scheduled, Alarm, COSEC, Motion Based, Manual
Optimization	Retention (Camera Wise Recording & Backup Retention)	Day wise(Configurable)
	Storage	Adaptive Recording: Automatically changes frame parameters during recording for configured time, thereby saving storage
	Bandwidth	Automatically adapts optimized resolution on local display through HDMI/VGA

Playback And Backup	Synchronous Playback	4 Channel
	Search Mode	Date and Time, Camera, Event, Recording Type
	Playback Modes	Fast Forward, Slow Forward, Slow Reverse, Fast Reverse at Different Speed Control, Next-Previous Frame
	Backup	Manual Backup over USB and NAS, Scheduled Backup over USB, NAS and FTP
	Network Functions	TCP/IP, DHCP, PPPOE DNS, DDNS, Free Matrix DNS, FTP, SMTP, NTP, RTP/RTSP, HTTP, CIFS/NFS, UPnP
	Remote Operation	Monitor, PTZ Control, Playback, System Setting, File Download, Log Information, Upgrade
Video Detection And Alarm	Trigger Events	Motion Detection, View Tampering, Connection Failure, Recording Failure, Manual Trigger, On Boot Alarm, Storage, Alert, Disk Volume Full, Disk Fault, Scheduled Backup Fail
	Actions	Recording on Selected Channel, Upload Images on FTP/Email server, Email Notification with Snapshot, TCP Notification, Recall PTZ Preset Position, Turn On/Off Alarm Outputs, Buzzer Notification, SMS Notification, Calling from Mobile App
	Motion Detection	Yes
	Connection Failure	Yes
	View Tamper	Yes
Interfaces	Communication Interface	1xGigabit RJ45 Ethernet Interfaces
	Throughput	144 Mbps (48 Mbps Downlink / 96 Mbps Uplink)
	USB	2 Ports (1x3G Connectivity, Mouse & 1xBackup)
Storage	SATA Interface	1 SATA Port (6TB Per Port)
	NAS	2 (16TB Per NAS)
	USB	1 TB USB Drive (GPT Partition Table)
System	Processor	High Performance Embedded Microprocessor
	OS	Linux
	Control Mode	Mouse, CMS and Web Client
Camera Support		Axis, Acti, Samsung, Panasonic, Sony, Planet, Zavio, Vivotek, LevelOne, Arecont Vision, Grandstream, Infinova, Dlink, Mobotix, Ganz and ONVIF 2.0 & above Support
Electrical	Power Input	12VDC, 5A
	Power Consumption	Less than 24W (with 1 HDD)
Environmental	Operating Temperature	0°C to +45°C (32°F to 113°F)
	Humidity Range	5% to 95% RH Non-Condensing
Mechanical	Dimensions (WxHxD)	360 X 46.45 X 153 mm
	Weight(Kg)	1.40 (without HDD)